Holemaking Solutions for Today's Manufacturing



Firearm manufacturers can set their sights on this. Allied Machine has solutions that are ideal for hole finishing on upper receivers for AR10 and AR15 firearms.

New specific ALVAN replaceable head style reamer mandrels provide the *long length of cut* you need.

These AR application specific reamer solutions are now **stocked standard** items and available to expedite your production.







ALVAN® Reamers Replaceable Head Style

- Diameter range: 11.80 mm 60.60 mm
- Heads are available as fixed or expanding for improved productivity
- Straight or left-hand helical flutes provide solutions for both through and blind holes
- Cylindrical shanks improve concentricity

Material: 6061 T6 Aluminum

CASE STUDY 215 UPPER RECEIVER

Measure	Carbide-Tipped Chucking Reamer	ALVAN® Replaceable Head Reamer	
RPM	1146	2559	
Speed	300 SFM	670 SFM	
Feed In	0.018 IPR (20.6 IPM)	0.045 IPR (115 IPM)	
Feed Out	0.018 IPR (20.6 IPM)	0.090 IPR (230.3 IPM)	
Finish	63 Ra	32 Ra	
Follow-Up Process	Roller Burnish	None	
Cycle Time	0:00:55	0:00:09	
Cost Per Hole	\$0.77	\$0.26	
Total Parts	3,500	3,500	
Total Cost	\$2,691.18	\$933.84	

NOTE: For improved hole quality, a speed reduction on entry may be required. Please consider a preceeding milling or shallow reaming operation to function as a guide for the long length reamer.



AR10 and AR15 Upper Receiver Solutions

01

02 🗉



03 ——

01

Mandrel - Designed specifically for AR10 and AR15 upper receivers

(Available as stocked standard items and ready to ship)

L₁

L₂

Radial coolant for through holes.

	itadia coolairioi anotigi notes.						
	Mandrel						
Firearm	D ₁	L ₂	L ₁	D ₂	No. of Teeth	Part No.	
AR10	1.1875"	9.65"	11.65"	0.750"	6	7000-MC-AR10	
AR15	1.0010"	8.66"	10.63"	0.750"	6	7000-MC-AR15	



02

Head -

New items designed specifically for AR10 and AR15 upper receivers

(NOW AVAILABLE as stocked standard items and ready to ship)

Firearm	Diameter	Tolerance*	No. of Teeth	Part No. (Uncoated)	Part No. (TiCN coated)	Fixed Screw
AR10	1.1875"	H7 (+0.0010"/-0)	6	17700-KLE-11875	I7700-KCE-11875	7000-VI-005
AR15	1.0010"	H7 (+0.0008"/-0)	6	I7700-KLE-10010	I7700-KCE-10010	7000-VI-004



*Reamer heads are manufactured to the high end of the tolerance specification for AR applications.

Or item number is customized to your specifications

(Must be ordered separately. See below for lead times)

		Fixed Heads			Expandable Heads		
	Coated/Uncoated	1 - 5 pcs	6 - 19 pcs	20+ pcs	1 - 5 pcs	6 - 19 pcs	20+ pcs
Lead Time (Work Days)	Coated	20	25	25	20	25	30
	Uncoated	15	20	20	15	20	25

Ordering the Reamer Head

Your head item number is customized to your tolerance needs. Refer to page C: 12 - 13 of the Allied Master Product Catalog for the guide to create your item number. Remember, for your reamer head, you must select the lead angle, the substrate, the flute style, and the coating when creating your item number.

NOTE: Both fixed and expandable heads are available for recondition.

03

Screw - Connect the head to the mandrel (Available as stocked standard items and ready to ship)

Fixed Screw					
Part No.	Н	Firearm			
7000-VI-005	6 mm	AR10			
7000-VI-004	5 mm	AR15			



Expanding Screw					
Part No.	Н	Firearm			
7000-VI-030	8 mm	AR10			
7000-VI-025	6 mm	AR15			





Allied Machine offers expert engineering support. Whether you need a quote, a test, or an application solution, a highly skilled and trained engineer is standing by, ready to help. www.alliedmachine.com/contactus

